



# STP-H2S-2 Series

## Super High Speed Fully Automatic 2 Track Hot-cut T-Shirt Bag Making Machine with Air Tension control

Shapes of product:




350 pcs/ minute Line




Standard device with the machine


Turn-up sealing design



Air tension control



Auto Unwind device




### FEATURES :


- ※ Super high speed operation. Capacity : Max. 2\*350 pcs/min. ( 700pcs/min)
- ※ High speed auto-punch system. **1 Punching cycle with folding just 10sec.**
- ※ 2 sets servo system with 2 mark sensor, can produce 2 lines printed T-shirt bag.
- ※ Turn-up Sealing bar design, easy to clean and maintain.
- ※ Hot-cut sealing with 4 temperature controllers; the sealing keep high quality.
- ※ Feed auto speed control by inverter and air tension control.
- ※ Block or no film auto stop; no film pre-connect device make film change faster.
- ※ All system by H.M. I. and P.L.C. control, all-function display, maintenance.
- ※ Heavy duty lifting auto unwind and Air shaft easy to put film roll.

### STP-H2S-2 Series

Mark Photo Sensor




In-Feed Guide



In-Feed Roller



Folding system



Punching and Clamp




End Film Gate



Auto Unwind device




Air tension



Punch control System



Turn-up Sealing



Smooth air device



Servo control System



### SPECIFICATION :

Model 型式	Bag Width line x W (max) 袋宽/膜厚 (mm)	Bag Length/ Film thickness 袋长/膜厚 (mm)	Max-Cutting of Punch 有效冲切(mm)	Capacity 产能 (pcs/ min/ line)	Main Motor/ Servo Motor 主马达 / 伺服 电机 (电功率/台)	Power Required 全台需电容量	Air supply Required 空压需求	Machine Size 机器尺寸 L x W x H (M)	Packing Size 装箱尺寸 L x W x H (M)	N.W./G.W. 净重 / 毛重 (Kg) Container size	
STP-800H2S-2	2 x 360	300~700/ 0.008~0.035	Thickness of pile Max. 20 mm	Max. 350*2	2Hp 4P/ 4.5 KW x 2	1.8 KW x 4 (7.2KW)	15 KW	0.6 Mpa 400ml / min	7.5 x 1.7 x 1.95	Sealing machine 2.35 x 1.75 x 1.95 Punch machine 1*2.0 x 1.7 x 2.2 1*20 ft / set	4000 / 4500
STP-1000H2S-2	2 x 460	300~700/ 0.008~0.035	Thickness of pile Max. 20 mm	Max. 350*2	2Hp 4P/ 4.5 KW x 2	2.2 KW x 4 (8.8KW)	16.5 KW	0.6 Mpa 400ml / min	7.5 x 1.9 x 1.95	Sealing machine 2.35 x 1.95 x 1.95 Punch machine 1*2.0 x 1.9 x 2.2 1*20 ft / set	4500 / 5000
STP-1200H2S-2	2 x 560	300~700/ 0.008~0.035	Thickness of pile Max. 20 mm	Max. 350*2	2Hp 4P/ 4.5 KW x 2	2.5 KW x 4 (10KW)	18 KW	0.6 Mpa 400ml / min	7.5 x 2.1 x 1.95	Sealing machine 2.35 x 2.15 x 1.95 Punch machine 0.9*2.0 x 2.2 x 2.2 1*20 ft / set	5500 / 6000
STP-500HS-1	1 x 460	300~700/ 0.008~0.035	Thickness of pile Max. 20 mm	Max. 350*1	2Hp 4P/ 4.5 KW x 1	2.2 KW x 2 (4.4KW)	8.5 KW	0.6 Mpa 400ml / min	7.5 x 1.4 x 1.95	Sealing machine 2.35 x 1.95 x 1.95 Punch machine 1*2.0 x 1.3 x 2.2 1*20 ft / set	3000 / 3400



Acerpack Plastic Machine Co ; Ltd.

Website: <http://www.acerpack.com>

E-mail: [service@acerpack.com](mailto:service@acerpack.com)